

FARAGAM PETRO TECH

Design, Materials Supply & Implementing Projects of Oil, Gas & Petrochemical

Date:

No:

Att:

ARAGAM PETRO TECH FARAGAM PETRO TECH FARAGAM PETRO TECH

Residue Wax (Foots Oil)

Match Grade

General Specification of Residue Wax (Foots oil) - Match Grade

Residue wax, is remained product after processing or de-oiling slack wax, when the slack wax pressurized to taking out specified oil percent for making paraffin wax. Residue wax has too much oil, up to 50%. Because of using a lot in making match industries, residue wax is called Foots Oil, as well. Our products are producing by full QC supervision according to the ASTM standard and will be guaranteed by Faragam Petro Tech Company.

Application of Residue wax (Foots oil) – Match Grade

Residue wax, is commonly used in making match industries. Also, Residue wax is applying in shoe making, Plastic, Polishing and wood industries. Meanwhile, residue wax use as lubricant, Grease row material, making tires, by its own properties.

Packing for Residue wax (Foots oil) – Match Grade

Our Residue Wax, is packing in some different types according to the customer order. Residue wax offered in Bulk liquid by Tankers, in 500-100 kg Jumbo bag or pack in new/second hand drums.

Technical Specification of Residue wax (Foots oil) – Match Grade

TEST/PROPERTY	RESULT/VALUE	METHOD
Oil Content	40-50	ASTM D721
Flash Point	215-225	ASTM D92
Melting Point	40-45	ASTM D87
Color @ 70°c	2-3.5	ASTM D1500



#73,10th Floor, Marjan Tower, Sattarkhan Street, Teharan, Iran

Tel No.: 021-44223804,021-44226991

Fax No.: 021-44254066 Postal Code: 1451875669

www. faragam-co.com

E-mail:info@faragam-co.com