



Paraffin wax 1-3% oil

(Semi Refined)

General Specification of paraffin wax 1-3% oil content

This type of paraffin wax, identifying by semi refined paraffin wax category. The main ingredient of, 1-3% semi refined paraffin wax is light or heavy slack wax. Heavy or light slack waxes as raw material have impression on melting point of semi refined paraffin wax 1-3%, between 58 to 65°C. This differences allow to the customers to choose inquired paraffin wax according to its own country temperature and location. The heavy one often used in nearest countries to the equator. Paraffin wax 1-3% oil, is transparent, white, too hard, non-odor. Our products are producing by full QC supervision according to ASTM standard and will be guaranteed by Faragam Petro Tech Company.

Application of semi refined paraffin wax 1-3% oil content

Paraffin wax 1-3% oil content commonly use in candle making because of its own property such as proper oil content, whitening grade.

Semi refined Paraffin wax 1-3% oil content is used for, PVC pipe and fitting producing, Paint Industries, coating and polishing.

Packing for semi refined Paraffin wax 1-3% oil content

Our semi refined Paraffin wax 1-3% oil content products are proposing in 5-6 kg slabs. Each 5 slabs packed in a PP bags then pack in a, 30 kg carton box. This carton box will be shrink.

According to the customer order palletizing of semi refined Paraffin wax 1-3% oil content, cartons is possible.

Technical Specification of semi refined paraffin wax 1-3% oil content

PROPERTIES	VALUE/RESULTS	METHOD
Oil Content	1-3% Max.	ASTM D721
Penetration	28-32 (0.1 mm)	ASTM D1321
Kinematic Viscosity @ 100°C	6-6.5 cst	ASTM D445
Color	0.6 y	ASTM D1500
Melting Point	62-66°C	ASTM D87
Flash Point	250°C Min.	ASTM D92

