



FARAGAM PETRO TECH

Design , Materials Supply & Implementing Projects of Oil ,Gas & Petrochemical

Date:

No:

Att:

FARAGAM PETRO TECH FARAGAM PETRO TECH FARAGAM PETRO TECH

Slack Wax Heavy Grade

Slack wax is extracted from refinery Rafinete after producing this product with solvents, which is mostly obtained from lubricant oil. Slack wax, has oil content up to 35%. According to processing and shape of Slack Wax, it is used in some industries. This product is raw material of paraffin wax. Slack wax divided to two grades, Heavy Grade and Light Grade.

Slack wax heavy grade is darker than light grade. The melting point up to 68 degrees, which can be of advantage.

Slack Wax Heavy Grade, Application

Slack wax, Heavy Grade is most commonly used in wax emulsions, as binders and water-proofing in artificial woods; in matches; in jar candles; in rust-protection products; in industrial lubricants; in arena-footing; in soil or turf protection; and in fireplace products.

Slack Wax Heavy Grade, Packing

Slack Wax is packing in steel and plastic drums. Also, it can be packed in customized pack referring to the client order, such as poly bag, liner carton box.

Technical Specification of Slack Wax Heavy Grade

PROPERTIES	VALUE/RESULTS	METHOD
Oil Content	12-15%	ASTM D721
Density@ 15.6°C(gr/cm3)	0.81-0.84	ASTM D4052
Color@ 70°C	3 max.	ASTM D1500
Melting Point	67°C	ASTM D87
Flash Point	240°C Min.	ASTM D92
Congeaing Point	58-60°C	ASTM D938



#73,10th Floor,Marjan Tower,Sattarkhan Street, Teharan,Iran

Tel No.: 021-44223804,021-44226991

Fax No.: 021-44254066 Postal Code : 1451875669

www. faragam-co.com

E-mail:info@faragam-co.com